

Coast Guard, DHS

§ 39.10-3

Subpart 39.20—Design and Equipment

- 39.20-1 Vapor collection system—TB/ALL.
- 39.20-3 Cargo gauging system—TB/ALL.
- 39.20-7 Tankship liquid overfill protection—T/ALL.
- 39.20-9 Tank barge liquid overfill protection—B/ALL.
- 39.20-11 Vapor overpressure and vacuum protection—TB/ALL.
- 39.20-13 High and low vapor pressure protection for tankships—T/ALL.

Subpart 39.30—Operations

- 39.30-1 Operational requirements—TB/ALL.

Subpart 39.40—Lightering and Topping-Off Operations with Vapor Balancing

- 39.40-1 General requirements for vapor balancing—TB/ALL.
- 39.40-3 Design and equipment for vapor balancing—TB/ALL.
- 39.40-5 Operational requirements for vapor balancing—TB/ALL.

AUTHORITY: 33 U.S.C. 1231; 46 U.S.C. 3306, 3703, 3715(b); 45 FR 58801, 3 CFR, 1980 Comp., p. 277; Department of Homeland Security Delegation No. 0170.1.

SOURCE: CGD 88-102, 55 FR 25446, June 21, 1990, unless otherwise noted.

Subpart 39.10—General

§ 39.10-1 Applicability—TB/ALL.

(a) Except as specified by paragraph (c) of this section, this part applies to each tank vessel operating in the navigable waters of the United States, when collecting vapors of crude oil, gasoline blends, or benzene emitted from a vessel's cargo tanks through a vapor control system.

(b) A tank vessel which transfers vapors of flammable or combustible cargoes other than crude oil, gasoline blends, or benzene, to a facility covered by 33 CFR part 154 must meet the requirements prescribed by the Commandant (G-MSO).

(c) A tank vessel with an existing vapor collection system specifically approved by the Coast Guard for the collection of cargo vapor which was operating prior to July 23, 1990, is subject only to § 39.30-1 and § 39.40-5 of this part as long as it transfers cargo vapor only to the specific facilities for which it was approved.

(d) This part does not apply to the collection of vapors of liquefied flam-

mable gases as defined in § 30.10-39 of this subchapter.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§ 39.10-3 Definitions—TB/ALL.

As used in this part:

Cargo deck area means that part of the weather deck that is directly over the cargo tanks.

Existing vapor collection system means a vapor collection system which was operating prior to July 23, 1990.

Facility vapor connection means the point in a facility's fixed vapor collection system where it connects with the vapor collection hose or the base of the vapor collection arm.

Independent as applied to two systems means that one system will operate with a failure of any part of the other system except power sources and electrical feeder panels.

Inerted means the oxygen content of the vapor space in a cargo tank is reduced to 8 percent by volume or less in accordance with the inert gas requirements of § 32.53 or § 153.500 of this chapter.

Lightering or *lightering operation* means the transfer of a bulk liquid cargo from a tank vessel to a service vessel.

Marine Safety Center means the Commanding Officer, U.S. Coast Guard Marine Safety Center, 1900 Half Street, SW, Suite 1000, Room 525, Washington, DC 20024 for visitors. Send all mail to Commanding Officer, U.S. Coast Guard Marine Safety Center, JR10-0525, 2100 2nd Street, SW., Washington, DC 20593, in a written or electronic format. Information for submitting the VSP electronically can be found at <http://www.uscg.mil/HQ/MS>.

Maximum allowable transfer rate means the maximum volumetric rate at which a vessel may receive cargo or ballast.

New vapor collection system means a vapor collection system which is not an existing vapor collection system.

Service vessel means a vessel which transports bulk liquid cargo between a facility and another vessel.

Topping-off operation means the transfer of a bulk liquid cargo from a service vessel to another vessel in

order to load the receiving vessel to a deeper draft.

Vapor balancing means the transfer of vapor displaced by incoming cargo from the tank of a vessel receiving cargo into a tank of the vessel or facility delivering cargo via a vapor collection system.

Vapor collection system means an arrangement of piping and hoses used to collect vapor emitted from a vessel's cargo tanks and to transport the vapor to a vapor processing unit.

Vapor control system means an arrangement of piping and equipment used to control vapor emissions collected from a vessel. It includes the vapor collection system and vapor processing unit.

Vapor processing unit means the components of a vapor control system that recovers, destroys, or disperses vapor collected from a vessel.

Vessel vapor connection means the point in a vessel's fixed vapor collection system where it connects with the vapor collection hose or arm.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by USCG-2007-29018, 72 FR 53965, Sept. 21, 2007]

§ 39.10-5 Incorporation by reference—TB/ALL.

(a) Certain materials are incorporated by reference into this part with the approval of the Director of the Federal Register in accordance with 5 U.S.C. 552(a). To enforce any edition other than the one listed in paragraph (b) of this section, notice of change must be published in the FEDERAL REGISTER and the material made available to the public. All approved material is on file at the U.S. Coast Guard, Office of Operating and Environmental Standards (G-MSO), 2100 Second Street, SW., Washington, DC 20593-0001, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. All material is available from the sources indicated in paragraph (b) of this section.

(b) The material approved for incorporation by reference in this part, and the sections affected are:

<i>American Petroleum Institute (API)</i> , 1220 L Street NW., Washington, DC 20005	
API Standard 2000, Venting Atmospheric and Low-Pressure Storage Tanks (Nonrefrigerated and Refrigerated), Third Edition, January 1982 (reaffirmed December 1987)	39.20-11
<i>American National Standards Institute (ANSI)</i> , 11 West 42nd Street, New York, NY 10036	
ANSI B16.5, Steel Pipe Flanges and Flanged Fittings, 1981	39.20-1
<i>American Society for Testing and Materials (ASTM)</i> , 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959	
ASTM F 1271-90 (1995)—Standard Specification for Spill Valves for Use in Marine Tank Liquid Overpressure Protection Applications	39.20-9
<i>International Electrotechnical Commission (IEC)</i> , Bureau Central de la Commission Electrotechnique Internationale, 1 rue de Varembe, Geneva, Switzerland	
IEC 309-1—Plugs, Socket-Outlets and Couplers for Industrial Purposes: Part 1, General Requirements, 1979	39.20-9
IEC 309-2—Plugs, Socket-Outlets and Couplers for Industrial Purposes: Part 2, Dimensional Interchangeability Requirements for Pin and Contact-tube Accessories, 1981	39.20-9
<i>National Electrical Manufacturers Association (NEMA)</i> , 2101 L St. NW., Washington, DC 20036	
ANSI/NEMA WD6—Wiring Devices, Dimensional Requirements, 1988	39.20-9
<i>National Fire Protection Association (NFPA)</i> , 1 Batterymarch Park, Quincy, MA 02269	
NFPA 70—National Electrical Code, 1987	39.20-9
<i>Oil Companies International Marine Forum (OCIMF)</i> , 15th Floor, 96 Victoria Street, London SW1E 5JW, England	
International Safety Guide for Oil Tankers and Terminals, Third Edition, 1988	39.30-1